



TST100 1-Wire temperature sensor



Short description

TST100 is 1-Wire temperature sensor.

The temperature sensor integrates a band-gap temperature sensor element plus signals processing and provides a fully calibrated digital output.

The sensor utilizes special flat aluminum head. It allows direct object assembly. The direct assembly ensures low thermal resistance, respectively fast response of the system.

The temperature sensor has 1 meter cable with soldered wires for direct connection to the screw terminals of controller.

Applications

- Server room and data centers temperature monitoring and logging.
- Temperature monitoring of industrial processes.
- Harsh environmental temperature monitoring.
- Temperature monitoring and logging for mobile operator facilities, vineyards, greenhouses, etc.

Technical parameters

Parameter	Value	Units	Remark
Operating Range	-40 to 85	°C	
Accuracy (max)	±0.5	°C	-10 to 85°C
Accuracy (max)	±2.0	°C	-40 to 85°C
Resolution	0.1	°C	
Supply voltage	3 to 5.5	VDC	
Ingress protection	IP65		
Head's dimensions	8 x 8 x 23 mm		
Connectors	LIYY cable - 1 meter		



control solutions

TERACOM

TST100 - 1-Wire temperature sensor

Usage

Can be used with following TERACOM controllers

- TCW241
- TCW220
- TCG120
- TCW122B-CM
- TCW122B-WD
- TCW112-CM
- TCW112-WD

Pinout

Signals	Cable colors
VDD (+ 3 to + 5.5V)	Yellow
Data	Green
GND (Ground)	Brown

Wiring example

Ethernet controller TCW122B-CM

TST100



1-Wire Bus

1-Wire is a registered trademark of Maxim Integrated Products, Inc. We strongly recommend read Maxim's 1-Wire tips at <http://www.maxim-ic.com/app-notes/index.mvp/id/148>.